TAL SCREEDBINDER®



DESCRIPTION

TAL SCREEDBINDER is a modified latex liquid additive designed for use with TAL SUPERSCREED, enhancing the bond strength and flexibility of TAL SUPERSCREED.

APPLICATION

TAL SCREEDBINDER should be used in place of water in the TAL SUPERSCREED mix when TAL SUPERSCREED is applied in high traffic areas, exterior or exposed areas, where building movement is expected (ie suspended slabs), and where thermal expansion and contraction is expected (ie under tile heating).

MIXING

The recommended mix ratio is 5ℓ TAL SCREEDBINDER mixed with 20kg TAL SUPERSCREED. Any water added to TAL SCREEDBINDER dilutes the polymer and will weaken the mix strength. Always add TAL SUPERSCREED to TAL SCREEDBINDER while mixing, and mix until a smooth, lump-free paste is obtained.

PACKAGING

TAL SCREEDBINDER is available in 5ℓ and 25ℓ bottles, and 200ℓ returnable drums.

STORAGE & SHELF LIFE

When stored in dry internal conditions between 5°C and 30°C and out of direct sunlight the product has a shelf life of 6 months from date of manufacture. Never store directly on a concrete floor.

WARNING DO NOT INGEST. USE ONLY AS DIRECTED. PROTECT SENSITIVE SKIN WITH RUBBER GLOVES.

TAL GUARANTEE

TAL products are manufactured and tested to TAL procedures, which are maintained in accordance with Quality System Standard ISO 9001 : 2000. TAL products are guaranteed to be free from manufacturing defects and fit for design purposes. TAL guarantees the performance of its products when used strictly in accordance with TAL's materials and methods specifications and good working practice.

TAL TECHNICAL ADVICE CENTRE

For a detailed Materials and Methods Specification contact the TAL Technical Advice Centre on 0860 000 TAL(825), or e-mail taltech@norcrossa.com. Branches : Johannesburg (011)316-3133; Cape (021) 386-1810; Natal (031) 700-1535

PRECAUTIONS

Contact TAL (Pty) Ltd for further health and safety information. Dispose of this product in accordance with local regulations.

IMPORTANT NOTICE

TAL believes the information on this sheet to be correct – but does not guarantee its accuracy or completeness. Conduct your own tests of this product to determine its suitability for intended use. User assumes all risks and liability during testing and use of this product. The only obligation of TAL shall be to replace any of this product proved to be defective in material. TAL shall not be liable for any injury, loss or damage, direct or inconsequential, relating to the use or inability to use this product. Except as expressly provided above, all products sold and samples furnished without any warranty of merchantability or any other warranty, express or implied. TAL (Pty) Ltd reserves the right to change the information on this datasheet.



Another successful installation guaranteed