

Concrete remover and etch

Product Description

TAL ACIDWASH is an acidic solution specifically developed to remove cement and concrete from most surfaces and to etch concrete prior to receiving finishes.

Advantages

- Quick results
- Easy to use
- Cost effective
- Rinses freely and easily with water

Uses

- Floor preparation
- Preparation of walls to receive coatings and paints
- Cleaning of cement and concrete from tools

Packaging

25 liter drums

Shelf Life

24 months when stored under shade in a dry environment.
Do not allow to freeze.

Installation Guidelines

Application

It is essential that long sleeve coveralls, rubber boots, rubber gloves, a solvent mask and safety goggles are worn when using TAL ACIDWASH.

Surface Preparation of Walls and Floors

TAL ACIDWASH should be diluted prior to use. It can be used at a dilution rate of 1 part TAL ACIDWASH to 1 to 4 parts clean potable water. Dilute by adding TAL ACIDWASH to water.

Always start with the maximum dilution and carry out a trial area to determine effectiveness. Pre-wet the area to be etched and then brush in the diluted product using a scrubbing action. When the surface has stopped "fizzing", rinse with water. Several applications may be required to obtain the desired surface finish.

Cleaning of Concrete from Tools and Equipment

Use at the 1 to 1 dilution rate. Using a stiff brush, work the diluted product into the hardened concrete and then remove using a scraper or wire brush. Rinse thoroughly with clean water after removing the concrete.